

Main Specification

Magnification	0.59X	0.625X	0.67X
Working Distance	260.5±5	249.7±5	237.5±5
Image Distance	138.6±2.5	142.6±2.5	147.6±2.5
Conjugate Distance	465.7±9	458.9±9	451.7±9
Flange Focal Distance	163±0.5	166.9±0.5	172±0.5


Image space NA	0.082
Object space NA	0.051
Entrance pupil diameter	29.8
Entrance pupil position	41.5
Exit pupil diameter	31.26
Exit pupil position	-191.4

Max image	① φ82
F/#	3.8
EFL	116
FOV	26.2°
ENP Diameter	φ29.8
Distortion	0.001%
Structure	8G

IMAGE QUALITY		
AXIS	φ46.2	① φ82
200lp/mm	160lp/mm	160lp/mm

注：  
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE:  
LINEARITY TOLERANCES ±0.05  
ANGULAR TOLERANCES ARE ±30°  
DRAFT ANGLES AREA ±0.5°/SIDE



材料(环保)	单位	比例
-	MM	1:1

设计	名称	规格书	页码
校对	部番	LS1662C-SPEC	1/1
审核	商品代号		版本
批准			V1