



注：  
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

Main Specification				Image space NA	0.03
Magnification	2.5X $\triangle$	3X	3.5X	Object space NA	0.1
Working Distance	122.4 $\pm$ 5 $\triangle$	112.6 $\pm$ 5	105.5 $\pm$ 5	Entrance pupil diameter	35.7
Conjugate Distance	696.5 $\pm$ 9	759.5 $\pm$ 9	825.9 $\pm$ 9	Entrance pupil position	64.9
Flange Focal Distance	493 $\pm$ 0.5	565.5 $\pm$ 0.5	639 $\pm$ 0.5	Exit pupil diameter	38.4
Max image circle	$\phi 82$			Exit pupil position	-592
F/#	4.0-16				
EFL	120				
Distortion	0.005%				
IMAGE QUALITY					
AXIS	$\phi 46.2$	$\phi 66$	$\phi 82$	$\triangle$	1
100lp/mm	100lp/mm	80lp/mm	80lp/mm	标记	处数

TOLERANCE: LINEARITY TOLERANCES $\pm 0.05$ ANGULAR TOLERANCES ARE $\pm 30'$ DRAFT ANGLES AREA $\pm 0.5^\circ$ /SIDE			材料(环保)	单位	比例
				mm	1:1
设计		名称	LS1630L-P01规格图		页码
校对		代号	LS1630L-P01 SPEC		1/1
审核	刘勇	版本			2.0
批准	2025-06-16	变更日期			V02