


2/3" F2.0/25 C Mount

		Working distance			Optical Magnification		2/3" Field of View(mm)				
		mm					H	V			
Focal Length	f=25mm			5000	0.005X	1760	1300				
Max Diameter (Ratio)	F=1:2.0~11										
Picture Size	2/3"(8.8×6.6mm) 1/2"(6.4×4.8mm) 1/3"(4.8×3.6mm)			2000	0.0125X	704	520				
Angle (Working distance=100mm)	H	14.9°	10.8°					1000	0.025X	352	260
	V	11.2°	8.1°								
Object Dimension at M.O.D	D	18.5°	13.5°	800	0.031X	283.9	209.7				
	H	34.1mm	24.8mm	700	0.0357X	246.5	182.1				
	V	25.6mm	18.6mm	600	0.042X	209.5	154.8				
Distortion (TV)	<0.5%			500	0.05X	176	130				
Focus distance(min)	0.1m			400	0.0623X	141.3	104.3				
Flange back	17.526mm in air			300	0.083X	106.0	78.3				
Back focus	6.6mm in air			200	0.125X	70.4	52.0				
Filter screw size	M43×0.75			100	0.24X	36.7	27.1				
Front/Rear Effective Dia	Front ϕ 27.9mm Rear ϕ 10.6mm										
Mount	C-Mount										
Temperature Range	-10~+50°C										
Storage Temperature Range	-20~+60°C										
Working Wavelength	240nm~1000nm										

TOLERANCE:
 LINEARITY TOLERANCES \pm 0.05
 ANGULAR TOLERANCES ARE \pm 30'
 DRAFT ANGLES AREA \pm 0.5°/SIDE



材料(环保)

单位	比例
mm	15:1

设计	校对	审核	批准	名称	代号	页码	版本
				UV2501A-规格书		1/1	
				UV2501A-Spec			V01